Unser Angebot:

15-Units SIF-0655 NEW



Toyota Land Cruiser 200 (Diesel) Protection Level VPAM BRV-2009 VR7

Prj. 222037| ÖBH



Cubic capacity:

Max. power (kw/HP):

Max. torque (Nm):

Length [mm]
Width [mm]

Height [mm]
Ride height [mm]

4.4<mark>61 cm³</mark>

173 (232) at 3.600 rpm

615 at 2.200 rpm

ca. 4.950

ca. 1.980

ca. 2.000

280

Toyota Land Cruiser 200 GX-R Safari SPL Diesel (foreign countries version) Vehicle with G.C.C. specification (Golf-Staaten)

Ausstattung:

Drive type:

Permanent all-wheel drive with off-road gear reduction, centre differential

· Equipment:

resilent construction, rubber studs floor (no stuff trim)

· Colour outside:

White

Colour inside:

Standard - Beige

Gearbox type:

Electronically regulated automatic gearbox

Gears: 6

Door wedge and door retaining straps

- Reinforced door hinge (Capacity 2.300 kg) and pillars
- Run flat system Europlast (50km at 50km/h)
- Special Chassis from Eibach
- High performance brake system from AP Racing
- Armoured battery
- Armoured engine control unit
- Master switch
- Voltage monitor relay
- Heating windshield
- Interior lighting new
- · Manual, inspection script in German and English

Ein unverbindliches Fahrzeug Angebot von:


ALPa - G.A.T.T. International GmbH

S.-G.-R.108 90431 Nürnberg Phone +49 (0)911 6587497 Mobile +49 (0)172 8139913

E-Mail: alpa-gatt@t-online.de






















Ein unverbindliches Fahrzeug Angebot von:

ALPa - G.A.T.T. International GmbH

S.-G.-R.108 90431 Nürnberg Phone +49 (0)911 6587497

Mobile +49 (0)172 8139913

E-Mail: alpa-gatt@t-online.de

15-Units New Toyota Land Cruiser 200 (Diesel) Protection Level VPAM BRV-2009 VR7



TECHNICAL SPECIFICATION
Prj. 222037 | ÖBH
VIN: 15 pc.

1 BASIC VEHICLE

1.1 TECHNICAL DATA

Toyota Land Cruiser 200 GX-R Safari SPL Diesel (foreign countries version)

Vehicle with G.C.C. specification (Golf-Staaten) Cubic capacity: 4.461 cm³

Max. power (kw/HP): 173 (232) at 3.600 rpm Max. torque (Nm): 615 at 2.200 rpm

Gearbox type: Electronically regulated automatic gearbox

Gears:

Drive type: Permanent all-wheel drive with off-road gear reduction, centre differential

with Torsen lock, manually lockable

Equipment: resilent construction, rubber studs floor (no stuff trim)

Colour outside: White

Colour inside: Standard - Beige

2 DIMENSIONS

Length [mm] ca. 4.950
Width [mm] ca. 1.980
Height [mm] ca. 2.000
Ride height [mm] 280

3 WEIGHTS

Unladen weight [kg] ca. 4.500*

Total weight permitted by TÜV [kg] 5.400

Payload [kg] ca. 900

4 PROTECTION LEVEL

Ballistic protection in accordance with VPAM-BRV-2009 VR7

Calibre:7,62 x 51 Test:

Type: FMJ/PB/SC Shooting distance: 10 (+ 0,5) m

Projectile velocity: 830 (+/- 10) m/s"

Front Armour steel 90°
Pillars Armour steel 90°
Doors Armour steel 90°
Overlaps Armour steel 90°
Rear door Armour steel 90°

Windows Bulletproof glass/Polycarbonate 90°

(also windowscreen 90°)

^{*}Unladen weight is dependent of additional equipment

Blast protection in according with VPAM ERV-2010

Floor Protection against hand grenades 2xDM51
Roof Protection against hand grenades 2xDM51

Side area Blast of 12,5 kg PETN in block shape (distance: 4m)

With integrated EuroSID 2 Dummy

The armor extends from the front wall to the armored tailgate. There is no additional door in the

rear. Certification of a complete vehicle

The vehicle has been tested and certified in accordance with the bombardment guidelines VPAM BRV 2009 and VPAM ERV 2010.

5 STANDARD VEHICLE PROTECTION AND EQUIPMENT

Door wedge and door retaining straps	
reinforced door hinge (Capacity 2.300 kg) and pillars	
Aluminium-Heavy-duty wheel (8.5x18), Load 1.850kg	
Run flat system - Europlast (50km at 50km/h)	
Special – Chassis from Eibach	
High performance brake system from AP Racing	
Armoured battery	
Armoured engine control unit	
Master switch	
Voltage monitor relay	
Heating windshield	
Interior lighting new	
Manual, inspection script in German and English	


6 ADDITIONAL OPTIONS INCLUSIVE

Elektrik		
LC-EL001	External power supply 230-V on the left rear bumper	
LC-EL003	External communication system (GSA - intercom system)	
	Parking heater – Webasto Thermo Top	
	Parking sensors - Dometic MagicWatch MWE 9008	
Karosserie		
LC-KA002	Electric windows for driver and front passenger (approx. 120 mm)	
	Separating grille between trank and passanger cell	
	Window tinting from the B-pillar	
	2 pairs of snow chains & spacers	
	1 pc. jack incl. 2 pcs. blocks and 1 pc. adapter	

7 OTHERS

7.1 ANTENNA POSITION

Rear left roof area with roof rack attachment.



3 PHOTOS



Additional information for offer no. 2220100259

Changes to the original Toyota equipment list:

- 8-seater: the 2 folding bench seats in the trunk are dismantled: the vehicle is classified as a 5-seater
- Antenna Glass: Not applicable: new antenna is moved outside the protected area
- Side Glass (UV Cut Green): Not applicable tinting technically possible, but only desirable from the B pillar due to approval
- Windshield green laminated: Not applicable tinting technically possible, but only desirable from the B pillar due to approval
- Owner Manual: German operating instructions for Manufacturer scope of delivery
- Cup Holder: Omitted Between the driver and front passenger seat as the controls for additional Manufacturer electronics are installed in this: main switch, window lifter, intercom
- Power Windows: Not applicable, only driver and passenger windows can be opened electrically approx. 120mm

